



Linksys Phone Adapter Configuration

Router

Voice

[Info](#) | [System](#) | [SIP](#) | [Provisioning](#) | [Regional](#) | **Line 1** | [PSTN Line](#) | [User 1](#) | [PSTN User](#) | [Ser Login](#) | [basic](#) | [advanced](#)

Line Enable: yes

Streaming Audio Server (SAS)

SAS Enable: no

SAS DLG Refresh Intvl: 30

SAS Inbound RTP Sink:

NAT Settings

NAT Mapping Enable: yes

NAT Keep Alive Enable: yes

NAT Keep Alive Msg: \$NOTIFY

NAT Keep Alive Dest: \$PROXY

Network Settings

SIP ToS/DiffServ Value: 0x68

SIP CoS Value: 3 [0-7]

RTP ToS/DiffServ Value: 0xb8

RTP CoS Value: 6 [0-7]

Network Jitter Level: high

Jitter Buffer Adjustment: up and down

SIP Settings

SIP Transport: UDP

SIP Port: 5060

SIP 100REL Enable: no

EXT SIP Port:

Auth Resync-Reboot: yes

SIP Proxy-Require:

SIP Remote-Party-ID: no

SIP GUID: no

SIP Debug Option: none

RTP Log Intvl: 0

Restrict Source IP: no

Referor Bye Delay: 4

Refer Target Bye Delay: 0

Referee Bye Delay: 0

Refer-To Target Contact: no

Sticky 183: no

Auth INVITE: no

Call Feature Settings

Blind Attn-Xfer Enable: no

MOH Server:

Xfer When Hangup Conf: yes

Proxy and Registration

Proxy: comtube.com

Outbound Proxy:

Use Outbound Proxy: no

Use OB Proxy In Dialog: yes

Register: yes

Make Call Without Reg: no

Register Expires: 3600

Ans Call Without Reg: no

Use DNS SRV: yes

DNS SRV Auto Prefix: yes

Proxy Fallback Intvl: 3600

Proxy Redundancy Method: Normal

Voice Mail Server:

Mailbox Subscribe Expires: 2147483647

Subscriber Information

Display Name:

User ID: 287412

Password: *****

Use Auth ID: no

Auth ID:

Mini Certificate:

SRTP Private Key:

Supplementary Service Subscription

Call Waiting Serv: yes
Block ANC Serv: yes
Cfwd All Serv: yes
Cfwd No Ans Serv: yes
Cfwd Last Serv: yes
Accept Last Serv: yes
CID Serv: yes
Call Return Serv: yes
Call Back Serv: yes
Three Way Conf Serv: yes
Unattn Transfer Serv: yes
VMWI Serv: yes
Secure Call Serv: yes
Feature Dial Serv: yes

Block CID Serv: yes
Dist Ring Serv: yes
Cfwd Busy Serv: yes
Cfwd Sel Serv: yes
Block Last Serv: yes
DND Serv: yes
CWCID Serv: yes
Call Redial Serv: yes
Three Way Call Serv: yes
Attn Transfer Serv: yes
MWI Serv: yes
Speed Dial Serv: yes
Referral Serv: yes
Service Announcement Serv: no

Audio Configuration

Preferred Codec: G711a
Use Pref Codec Only: no
G729a Enable: yes
G723 Enable: yes
G726-16 Enable: yes
G726-24 Enable: yes
G726-32 Enable: yes
G726-40 Enable: yes
DTMF Process INFO: yes
DTMF Process AVT: yes
DTMF Tx Method: AVT+INFO
FAX Process NSE: yes
FAX Disable ECAN: no
FAX Enable T38: yes
FAX Tone Detect Mode: caller or callee

Silence Supp Enable: no
Silence Threshold: medium
Echo Canc Enable: yes
Echo Canc Adapt Enable: yes
Echo Supp Enable: yes
FAX CED Detect Enable: yes
FAX CNG Detect Enable: yes
FAX Passthru Codec: G711u
FAX Codec Symmetric: yes
FAX Passthru Method: NSE
DTMF Tx Mode: Strict
Hook Flash Tx Method: None
Release Unused Codec: yes
FAX T38 Redundancy: 1
Symmetric RTP: yes

Gateway Accounts

Gateway 1:
GW1 Auth ID:
Gateway 2:
GW2 Auth ID:
Gateway 3:
GW3 Auth ID:
Gateway 4:
GW4 Auth ID:

GW1 NAT Mapping Enable: no
GW1 Password:
GW2 NAT Mapping Enable: no
GW2 Password:
GW3 NAT Mapping Enable: no
GW3 Password:
GW4 NAT Mapping Enable: no
GW4 Password:

VoIP Fallback To PSTN

Auto PSTN Fallback: yes

Dial Plan

Dial Plan: (*xx|[3469]11|0|00|[2-9]xxxxxx|1xxx[2-9]xxxxxxS0|xxxxxxxxxxxxxx.)
Enable IP Dialing: no
Emergency Number:

FXS Port Polarity Configuration

Idle Polarity: Forward
Callee Conn Polarity: Forward

Caller Conn Polarity: Forward

Undo All Changes

Submit All Changes

[User Login](#) | [basic](#) | [advanced](#)